


Construction is made from glued wood and plywood, stainless and galvanized steel metal, rope and HDPE and plastic details.




10
children




5 - 14
age



2,01 m
height of fall




85 kg
(heaviest part)



1535 kg



....
(without excavation and
concreting)




Length: **6 720 mm**
Width: **6 945 mm**
Height: **3 985 mm**

Length of safety area: **10 475 mm**
Width of safety area: **10 135 mm**
Required safety area: **81,77 m²**

(Install shock absorbing material according to
EN 1176:2017)

**Do not place stainless steel slide
directly to south!**




Foundation should be
accessible for maintenance.

Playground equipment steel foundation is concreted in the ground at the planned location. The equipment can be used after two days when the concrete becomes solid. During assembly no children are allowed in the area.

Equipment safety checkings must be performed once in a week in high vandalism risk area.

Maintenance is required once in every 3 months, depending on usage.




Transportation:

3 (three) palettes:
2 600 x 1 000 x 500 mm
3 400 x 1 000 x 500 mm
2 600 x 1 200 x 1 000 mm

Spare parts:

All needed spare parts and elements, when warranty time expires can be ordered in Jūrmalas Mežaparki Ltd., and all the goods will be ready for delivery in 5 working days.



According to EN 1176:2017

Manufactured
according:
07.11.2019.

